

## High Speed Optical Laser Hand Tachometer - LED display CT6/LSR/ERP

### Applications

This product has been evolved to facilitate the measurement of very high speed small shaft machines, such as dental drilling equipment, gyros, air motors and similar low torque high speed devices.

### Key Features

Bright red LED Display • Manual/Autorange modes • Remote sensor input • Last reading hold & re-call • Contact Adaptor fitment • On target & low battery indicators.

### Function - High speed mode

This product operates without reflective tape under controlled conditions, when using the LN1 adaptor. There is an integral sensitivity control which requires adjustment to suit the specific application conditions.

### Accessories

Remote optical sensors, mounting brackets, Spares for Contact adaptor, Reflective tape.

### Laser Optical System

Normal speed applications

Optical Range 50 - 2000mm

Optical angle +/- 80 deg.

### High Speed Mode

With LN1 Lens adaptor fitted Optical Range - nominally 50mm Target - a non reflective paint or material is required

Certificate of calibration.

### Safety of use

The Laser is classified CLASS II safe for portable use, the user must take care not to stare directly into the Laser Beam, this would have a similar dazzling effect as staring directly into a high power torch light or car headlight at close range!

**TTL 5v pulse output facility** - For datalogging and triggering purposes in vibration and balancing applications.

**Additional on/off switch** - To allow continuous measurement where required for data monitoring applications in hands free mode.

**Sensitivity control** - Necessary for setting the Laser on specific high speed applications when using the LN1 lens.

### General Specification

Basic RP range	3 rpm - 99,999 rpm
High speed mode	500,000 rpm +/-10
Resolution	max - 0.001 (auto) +/-10 rpm HS mode
Sensitivity	Adjustable externally
On Target Ind.	Yes
Power	4 x AA batteries
Memory	Last reading recall

### Other Measurement Ranges

Count mode	0 - 99999 revolutions
Resolution	0.1 metre or 1 rpm
Time accu.	0.01 - 99999 secs
Time int.	0.01 - 99999 secs
Accuracy	0.02% of reading +/- 1 digit



Order Code	Description
CT6/LSR/ERP	High Speed Laser Tachometer